Global Air King Universal Couplings

Hose Ends

Size	*Investment Cast Steel* Part #
1/2" 3/4" 1"	***GAM1*** ***GAM6*** ***GAM11***



Air King Ferrules

Size	Ferrule ID	*Investment Cast Steel* Part #
1/2"	0.906 1.120 1.149	***CCF0906*** ***CCF1120*** ***CCF1149***
3/4"	1.190 1.218 1.246 1.438	***CCF1190*** ***CCF1218*** ***CCF1246*** ***CCF1438***
1"	1.469 1.500 1.531	***CCF1469*** ***CCF1500*** ***CCF1531***

Offers a low profile streamline appearance with maximum retention.

- lightweight
- can be crimped
- *ONLY* to be used with the global air kig hose end, shown above

SAFETY ALERT



SAFETY ALERT

Air King is for air and water service only *Warning: Never use any Air King coupling for steam service!*
None of Dixon's catalog information is to be interpreted to mean that this type of coupling is suitable for use on steam hose.

Crimped Air King Recommendation Guide

½" Global Air King

Hose ID	Stem Part #	Ferrule Part #	Hose OD *Fractional*	Hose OD *Decimal*	Crimp Diameter (±0.005)	% Reduction
½"	***GAM1***	***CCF0906***	54/64	0.8438	0.840	15
		CCF0906	55/64	0.8594	0.853	15
		CCF0906	56/64	0.8750	0.867	15

¾" Global Air King

Hose ID	Stem Part #	Ferrule Part #	Hose OD *Fractional*	Hose OD *Decimal*	Crimp Diameter (±0.005)	% Reduction
¾"	***GAM6***	***CCF1120***	1-5/64	1.0781	1.082	20
		CCF1120	1-6/64	1.0938	1.094	20
		CCF1149	1-7/64	1.1094	1.107	20
		CCF1149	1-8/64	1.1250	1.119	20
		CCF1190	1-9/64	1.1406	1.122	20
		CCF1190	1-10/64	1.1563	1.134	20
		CCF1218	1-11/64	1.1719	1.147	20
		CCF1218	1-12/64	1.1875	1.159	20
		CCF1246	1-13/64	1.2031	1.182	20
		CCF1246	1-14/64	1.2188	1.194	20

1" Global Air King

Hose ID	Stem Part #	Ferrule Part #	Hose OD *Fractional*	Hose OD *Decimal*	Crimp Diameter (±0.005)	% Reduction
1"	***GAM11***	***CCF1438***	1-25/64	1.3906	1.388	20
		CCF1438	1-26/64	1.4063	1.400	20
		CCF1469	1-27/64	1.4219	1.413	20
		CCF1469	1-28/64	1.4375	1.425	20
		CCF1500	1-29/64	1.4531	1.438	20
		CCF1500	1-30/64	1.4688	1.450	20
		CCF1531	1-31/64	1.4844	1.463	20
		CCF1531	1-32/64	1.5000	1.475	20