



Model TD 2100°F Factory-Built Chimney Systems



TDSB* Support Band



- Chimneys with round vent terminations extending 5 feet or more above the roof must be braced.
- The support band provides a means of attaching bracing to the pipe.

Catalog Number	Dim. A
6TDSB	8"
7TDSB	9"
8TDSB	10"
10TDSB	12"
12TDSB	14"
14TDSB	16"





TDTC Cathedral Trim Ring

- For slopes above 16/12 to 36/12 pitch.
- Black finish two-piece trim ring with template for cutting to required pitch.
- Available in 6" - 10".



TDTR Cut-Out Trim Ring

- For slopes from flat to 12/12 pitch.
- Black finish one-piece trim ring with template for cutting to required pitch.
- The TDTR is used when a TDP chimney section is hung below the TDRS Roof Support.
- The TDTR will finish off the ceiling.
- Available in 6" - 10".




TDS* Storm Collar

- Storm collar is installed just above flashing.
- Use caulking material for watertight installation.


Catalog Number	Dim. A	Dim. B	Dim. C
6TDS	8"	10 7/8"	1 7/16"
7TDS	9"	11 7/8"	1 7/16"
8TDS	10"	12 7/8"	1 7/16"
10TDS	12"	15 1/2"	1 3/4"
12TDS†	14"	17 7/8"	1 15/16"
14TDS†	16"	20 1/4"	2 1/8"

† With draw-tight Clip



TDTS* Stainless Starter and Cleanout Tee

- Needed on chimneys with open termination to prevent rain from damaging appliance.
- Drip cap can be removed for cleanout and inspection.



Catalog Number	Dim. A	Dim. B
6TDTS	6"	23 1/4"
7TDTS	7"	24 1/4"
8TDTS	8"	25 1/4"
10TDTS	10"	27 1/4"
12TDTS	12"	29 1/4"
14TDTS	14"	31 1/4"

* Denotes U.L. Listing