

# BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - [www.boshart.com](http://www.boshart.com)

9-5

April 17/15

## SUPER-TIE ROPE HANGER

PART NO.	FITS CASINGS	ACCEPTS ROPE	WEIGHT	CTN	CASE	LIST PRICE-A
STRH-6	6" & 6-1/4" I.D.	1/4" - 3/8"	1.30 lb	5	40	17.73

NOTE: Brass easy tie rope adapters are available - See Section 4



## CABLE GUARDS

Cable guards will keep the power cable from abrading against the well casing. One should be placed at the pump and one every 15 ft there after. Furnished in 6" size, tabs can be cut off to fit 4" and 5" well casing also.



PART NO.	MODEL	DROP PIPE	UNIT WEIGHT	QUANTITY CASE	LIST PRICE-A
WG-6	Snap-In	1 & 1-1/4	1.5 oz		1.15
WG-100	Self-Clamping	1	2.0 oz	48	2.40
WG-125	Self-Clamping	1-1/4	2.0 oz	48	5.22

Snap-in cable guard (WG-6) will fit 1" & 1 1/4" drop pipe while the self-clamping cable guard WG-100 will only fit 1" pipe and WG-125 will only fit 1-1/4" pipe.



## PVC DROP PIPE COUPLINGS

- Machined using extruded PVC coupling stock
  - Wall thickness is 30% heavier than Schedule 120 to ensure increased strength and reliability
- Note: To be used in well depths no greater than 400'

PART NO.	SIZE	OVERALL LENGTH	QUANTITY CTN	QUANTITY CASE	WGT. PER 100 PCS.	LIST PRICE-A
28-PDPC-10	1"	2-3/4"	10	100	12 lbs	2.19
28-PDPC-12	1-1/4"	2-3/4"	10	100	14 lbs	2.66
28-PDPC-15	1-1/2"	2-3/4"	10	100	25 lbs	3.32
28-PDPC-20	2"	3"	10	100	34 lbs	4.14



## STAINLESS STEEL DROP PIPE COUPLINGS

**Boshart recommends -** Using both Gray Stainless Steel PTFE Tape & Gray Magic Pipe Thread Compound together for joining stainless steel threaded connections.

- Inside chamfer on both ends for trouble free starting of threads
- Separate taper to ensure proper watertight seal
- Flats on sides for ease of use with wrench
- Heavy duty construction 304 Stainless Steel



Third Party  
Certified to  
NSF / ANSI 372

PART NO.	SIZE	OVERALL LENGTH	QUANTITY CTN	QUANTITY CASE	WGT. PER 100 PCS.	LIST PRICE-A
28-SSDPC-10	1"	2-1/2"	10	50	72 lbs	11.26
28-SSDPC-12	1-1/4"	2-1/2"	10	50	87 lbs	13.18
28-SSDPC-15	1-1/2"	2-1/2"	10	50	116 lbs	16.69
28-SSDPC-20	2"	2-1/2"	5	25	134 lbs	19.71

