



**SADDLEGRIP®**  
**Connectors**

For aluminum and steel Flex • AC • MC cable. Zinc die-cast.



CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
SG38‡	18065	3/8	1/2	50	500	1.000	.400	1.077	.405-.612	.400
SG38A*‡	80138	3/8	1/2	50	500	1.090	.490	1.077	.405-.612	.400
SG380‡	18060	3/8	1/2	50	500	1.000	.400	1.077	.405-.612	.400 x .580
SG380A*‡	80140	3/8	1/2	50	500	1.090	.490	1.077	.405-.612	.400 x .580
SG40‡	01740	7/16	1/2	50	500	1.480	.480	1.125	.530-.790	.620
SG50‡	07500	1/2	1/2	50	500	1.480	.480	1.277	.710-.910	.620
SG50A*‡	37501	1/2	1/2	50	500	1.511	.511	1.277	.710-.910	.620
SG75	18075	3/4	3/4	20	200	1.435	.450	1.470	.840-11.10	.820
SG75A*	17751	3/4	3/4	20	200	1.466	.481	1.470	.840-1.110	.820

\*Provided with insulated throat.

‡Also for MCI-A (MC<sup>AP</sup>™ and HCF MC<sup>AP</sup>™) cable. Refer to page E-26 for cable ranges.

Refer to chart on page E-25 for a list of cable types.

Concrete tight when taped.


For cables smaller than .405" see L16 and L16ST on page E-5.



SG380



SG38



E60812 LR49636

**Duplex**  
**SADDLEGRIP®**  
**Connectors**

Zinc die-cast. For aluminum and steel Flex • AC • MC cable • MCI-A (MC<sup>AP</sup>™ and HCF MC<sup>AP</sup>™) cable.



CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
SG3838	17383	3/8	1/2	25	100	.452	1.526	.780	(2) .445-.612
SG3838A*	36205	3/8	1/2	25	100	.512	1.586	.780	(2) .445-.612



\*Provided with insulated throat.

Refer to chart on page E-24 for a list of cable types.

Refer to chart on page E-26 for MCI-A (MC<sup>AP</sup>™ and HCF MC<sup>AP</sup>™) cable ranges.

Concrete tight when taped.

With independent securing of the cables, you can use two different size cables.



E60812 LR49636